
COMPARISON OF HYPERSONIC AIRCRAFT QUASI HORIZONTAL MANEUVER CONTROL METHODS

T.A. Kalinovskiy

kalinovskiy.t@mail.ru

Bauman Moscow State Technical University, Moscow, Russian Federation

Abstract

We studied the movement and possible maneuvering of the advanced hypersonic aircraft in the Earth's atmosphere. We solved the problem of determining the maximum capacity of the system, the quality assessment of the control algorithms by comparing the calculated trajectory with the optimal (reference) one

Keywords

Hypersonic aircraft, control method, maneuvering, banking angle, atmosphere, optimal control

© Bauman Moscow State Technical University, 2016

References

- [1] Nesterenko G.N. Kosmicheskaya aviatsiya [Space aviation]. Moscow, VI Publ., 1969. 60 p. (in Russ.).
- [2] Mel'nikov A.Yu. Optimal'noe upravlenie manevrami giperzvukovogo planera na osnove printsipa maksimuma Pontryagina [Optimum control on hypervelocity glider evolution using Pontryagin's maximum principle]. Moscow, Bauman MSTU Publ., 2015. 14 p. (in Russ.).
- [3] Pyshnov V.S. Polet s bol'shimi dokosmicheskimi skorostyami [High pre-space speed flight]. Zhukovsky VVIA Publ., 1959. 59 p. (in Russ.).
- [4] Koryanov V.V., Kazakovtsev V.P. Osnovy teorii kosmicheskogo poleta. Ch. 1. [Space flight fundamentals. Part 1]. Moscow, Bauman MSTU Publ., 2013. 27 p. (in Russ.).
- [5] James M. Acton. Hypersonic boost-glide weapons. *Science and Global Security*, 2015, vol. 23, no. 3, pp. 191–219.

Kalinovskiy T.A. — student of the Department of Rocket and spacecraft dynamics and flight control, Bauman Moscow State Technical University, Moscow, Russian Federation.

Scientific advisor — A.Yu. Melnikov, Assistant of the Department of Rocket and spacecraft dynamics and flight control, Bauman Moscow State Technical University, Moscow, Russian Federation.