
ON DEVELOPING SPINDLE UNITS FOR HIGH-SPEED MACHINING

A.Zh. Beksultanova

aselyab_96@mail.ru

Bauman Moscow State Technical University, Moscow, Russian Federation

Abstract

We analysed the way that employing high-speed machining affects the increase in manufacturability. We consider special properties of machine tools: high geometric precision, static and dynamic rigidities, thermal stability, ensuring uninhibited chip flow.

Keywords

Electric drive, pneumatic drive, precision machine tool, high-speed machining, internal grinding machine

© Bauman Moscow State Technical University, 2017

References

- [1] Mutsyanko V.I., Stepanenko V.G., Filimonov L.G. Okunev B.A. High-speed finishing impact on surface quality. *Stanki i instrument*, 1979, no. 2.
- [2] Solonenko V.G., Ryzhkin A.A. Rezanie metallov i rezhushchie instrument [Metall cutting and cutting tools]. Moscow, Infra-M publ., 2011. 416 p.
- [3] Suslov A.G. Tekhnologiya mashinostroeniya [Mechanical engineering technology]. Moscow, Mashinostroenie publ., 2007. 430 p.
- [4] Vereina L.I. Implementation of high-speed cutting on operating machine-tool. *Remont. Vosstanovlenie. Modernizatsiya* [Repair, Reconditioning, Modernization], 2017, no. 1, pp. 40–43.
- [5] Cherpakov B.I., Vereina L.I. Tekhnologicheskoe oborudovanie mashinostroitelnogo proizvodstva [Technological equipment of machinery production]. Moscow, Publ. center “Akademiya”, 2005. 416 p.

Beksultanova A.Zh. — student, Department of Machine Tools, Bauman Moscow State Technical University, Moscow, Russian Federation.

Scientific advisor — L.I. Vereina, Cand. Sc. (Eng.), Assoc. Professor, Department of Machine Tools, Bauman Moscow State Technical University, Moscow, Russian Federation.
